





3, Table 2 General characteristics

Rated Vol. (V)	A Derated Vol. 125 (V)	B Derated Vol. 200 (V)	Nominal Cap. (μF)	Dissipation Factor +25 +85 +200 (%)	Leakage current (μA)		Impedance 100Hz -55 ()	Cap change rate (%)			85 40KHZ AC Ripple current (mA)	Case Code						
					+25	+85 +125		-55	+85	+200								
6	4	3.6	30	7	1	2	100	-40	+11	+15	820	T1						
			68	12			60				+14		+18	960				
			140	17			40						+20	1200				
						270	30	2	7	25	-44	+18	+25	1375	T2			
						330	30			20				+14		+20	1800	
						560	45			25				-64		+18	+25	1900
						1200	90			20								-80
8	5	4.8	25	7	1	2	100	-40	+11	+15	820	T1						
			56	10			59				+14		+18	900				
			120	15			50						+18	+20	1220			
			220	30	7	30	-44	+25	1370									
			290	30	2	6			25	-64	+18	1770						
			430	36		14	25	1825										
						850	50	4	16	22	-80	+25	+30	2330	T4			
10	7	6	20	5	1	2	175	-32	+11	+15	820	T1						
			47	11			100				+14		+18	855				
			100	12			60						-36	+20	1200			
			180	20	7	40	-40	+25	1365									
			250	25	2	10			30	-64	+18	1720						
			390	25		16	25	1800										
						750	40	4		23	-80	+25	+30	2360	T4			



Table 2 General characteristics

Rated Vol. (V)	A Derated Vol. 125 (V)	B Derated Vol. 200 (V)	Nominal Cap. (μF)	Dissipation Factor +25 +85 +200 (%)	Leakage current (μA)		Impedance 100Hz -55 ()	Cap change rate (%)			85 40KHZ AC Ripple current (mA)	Case Code			
					+25	+85 +125		-55	+85	+200					
30	20	18	8	4	1	2	275	-16	+8	+12	640	T1			
			15	5			175				-20		780		
			40	8			5				65	-24	+11	+15	1120
			68	11	8	60		+13		1285					
			100	15	2	10	40	-28	+11	+18	1450	T3			
			150	20		15	35	-48	+13	+25	1525				
			300	25	8	32	25	-60	+25	+35	1950	T4			
50	30	30	5	3	1	2	400	-16	+5	+9	580	T1			
			10	4			2				250		-24	+8	+12
			25	7			5				95	-20	+11	+15	1005
			47	10	8	70	-28	+13	+18	1155					
			60	10	2	10	45	-16	+11	+15	1335	T3			
			82	12		12	45	-32	+13	+18	1400				
			160	15	8	30	27	-50	+25	+30	1900	T4			
60	40	36	4	2.8	1	2	550	-16	+5	+9	525	T1			
			8.2	4			2				275		-24	+8	+12
			20	6			5				105	-16	+11	+15	930
			39	8	8	90	-28	1110							
			50	9	2	10	50	-16			1330	T3			
			68	10		10	45	-32			1365				
			140	12	8	30	28	-40	+20	+25	1850	T4			
			*560	50	30	160	25	-60	+40	+50	2800	T5			
75	50	45	3.5	2.5	1	2	650	-16	+5	+9	525	T1			
			6.8	3.5			2				300		-20	+8	+12
			15	5			5				150	-16			890
			33	8	9	90	-24	+11	+18	1000					
			40	8	2	10	60		-16	+15	1250	T3			
			56	10		12		-28	+18	1335					
100	65	60	110	10	9	30	29	-35	+20	+25	1850	T4			
			2.5	2	1	2	950	-16	+7	+10	505	T1			
			4.7	3							2		500	-20	565
			11	5							4	200	-16	+8	835
			22	6	9	100	-24			965					

Please read the important notes and cautions at the end of this document.



Please read the important notes and cautions at the end of this document.